

EcoPrO₃[™] 150G *Gaseous Ozone Treatment System*

The EcoPrO₃-150G Gaseous Ozone Treatment System is designed for extremely accurate setpoint gaseous ozone treatment of products and surfaces for mold and bacteria control. The system produces ozone gas at a rate of 150.0 grams/hour. It has an integrated UV absorption technology ozone concentration monitor with sample pump for setpoint control of ozone concentration in the space being treated.

- FULLY AUTOMATED DOSING CONTROL
- MOST ACCURATE UV ABSORPTION OZONE MONITORING TECHNOLOGY
- WEB-BASED REMOTE MONITORING AND DATA LOGGING
- SIMPLE, ECONOMICAL DESIGN

SPECIFICATIONS	
Gaseous Ozone Output	150.0 Grams/Hour
Gaseous Ozone Flow	20.0 LPM
Ozone Monitor	Included
Cooling Method	Air Cooled
Oxygen Feed Gas	20.0 LPM
Power Requirements	240VAC, 20A
Enclosure Rating	NEMA-3R
Dimensions	70.0"H x 44.0"W x 32.0"D
Weight	240 lbs.



Advanced
OZONE
Integration[™]

U.S. Headquarters:
2580 El Camino Real
Atascadero, CA 93422
Phone: (805) 464-2107

Canada Headquarters:
540 Newbold Street
London, Ontario / N6E 2S5
Phone: (519) 204-2909